

VPC Gas Cabinet Heater Range

Industrial & Commercial Heating Systems.



www.powrmatic.co.uk



Unit 5 Image Business Park
East Cannock Road, Cannock, WS12 1LT
Tel: 0845 5578085 Fax: 01543 876582
www.warmairheaters.com
office@warmairheaters.com



CE

HEATING // VENTILATION // AIR CONDITIONING

Model			30	52	80	110	130	
Output			kW	30	52	80	110	130
Electrics	Supply	Standard	V/ph/Hz	230/1/50				
		Optional	V/ph/Hz	415/3/50				
Overall dimensions		Height	mm	2257	2713	2804	2715	2298
		Width	mm	750	750	750	750	750
		Depth	mm	1108	1108	1412	1767	1767
Flue diameter			mm ø	100	100	130	130	130
Nett weight			kg	178	248	305	362	410

Notes:

- Dimensions and weights in table above refer to freeblowing heaters only

Introduction

Warm air heating provides an efficient, flexible and cost effective solution for the heating of most industrial and commercial buildings.

Powrmatic have been a leading manufacturer of warm air heating products for more than sixty years. Integrity of design and quality of manufacture are characteristics inherent in each and every product.

Peace of mind is assured with a comprehensive package which includes a two year parts and one year labour guarantee, as well as a TEN year heat exchanger warranty.

VPC Cabinet Heaters

The VPC range benefits from clean lines with a fully housed burner. To reduce installation costs these can be arranged for either flue only or room sealed flue having either vertical or low level horizontal discharge.

Models are provided for natural gas as standard or LPG firing upon request. All heaters are finished with a durable epoxy powder coat paint finish which is stove hardened.

Heat Exchanger

Four pass primary tubular assembly manufactured from aluminised steel formed, swaged and expanded without recourse to stress inducing welding. Designed and manufactured to combine thermal efficiency with long-lasting service life. Life cycle tested and warranted for ten years.

Powrmatic Ltd
Hort Bridge
Ilminster
Somerset
TA19 9PS

tel: +44 (0) 1460 53535
 fax: +44 (0) 1460 52341
 e-mail: info@powrmatic.co.uk
 web: www.powrmatic.co.uk



Powrmatic Ireland
45 Broomhill Close
Tallaght
Dublin 24

tel: +353 (0) 1452 1533
 fax: +353 (0) 1452 1764
 e-mail: info@powrmatic.ie
 web: www.powrmatic.ie



Time and Temperature Controls

Factory fitted time and temperature controls are supplied to provide automatic operation. Control options include the easy to set Powtrol or the code protected optimised start MC200BL/MC300-Multi. All control systems include, as standard, day thermostat, frost protection thermostat, programmable time switch and fan only switching to facilitate summer air movement.

Fuel Efficiency

Favorable levels of fuel usage are a key element of VPC heater design, additionally, all heaters have efficiencies which meet or exceed the requirements of current Part L2B Building Regulations.

