



A Sign of Quality

Specification

Tuffa 15000VB

TECHNICAL INFORMATION

Diameter:	2866mm
Height:	3650mm
Capacity:	15000 litres <i>This is reduced by the overfill prevention valve *</i>
Approx Weight:	700 kilograms
Material:	Medium density polyethylene
UV Stabilised:	Yes
Fill:	2" BSP

PRODUCT DESCRIPTION

15000 litres bunded tank.

SPECIFICATION

- ◇ A H&S approved fill point cabinet to house all appropriate Equipment, including low level fill
- ◇ 2" BSP fill connection c/w cap and chain
- ◇ Vent
- ◇ Contents gauge
- ◇ 1" bottom outlet (top outlet available upon request)
- ◇ Battery bund / overfill alarm located within the cabinet
- ◇ Overfill prevention valve *this reduces the working capacity.

OPTIONAL EXTRAS

- ◇ Fire Protection—The Tuffa FireStop is our patented Fire Protection for oil storage tanks and can be fitted to all of our Bunded range of tanks. It can be supplied in 30 / 60 minutes fire/thermal protection and 120 minute fire protection where required. It meets the methodology in BS5410: Part 1: Section 6.3 and the material is independently tested to BS476.
- ◇ Higher accuracy contents gauge
- ◇ Armco protection barrier
- ◇ High security steel cabinet with roller shutter door



Unit 5 Image Business Park
 East Cannock Road, Cannock, WS12 1LT
 Tel: 0845 5578085 Fax: 01543 876582
 www.warmairheaters.com
 office@warmairheaters.com

Issued 01.02.10



Your in-house Liquid Storage Solution Partners

Manufacturers of plastic and steel liquid storage tanks up to 100,000 litres.

Easi-fill Bunded Range

Easi-fill Fuel Stations

Interlinked Tanks

Dual & Triple storage compartment tanks

Biodiesel Storage

Tank Fire Protection

Waste Oil tanks, Bowsers & Chemical Tanks

Petrol Storage

Rain Water Harvesting

AdBlue Systems

T: 01889 567700
F: 01889 567600



www.tuffa.co.uk
sales@tuffa.co.uk



Registered office address:

TUFFA UK Limited
Dovefields Industrial Estate
Derby Road
Uttoxeter
Staffordshire



VAT Reg No.: 861 420 544
Company Reg: 5444911

